

QS3; QS5

Quadro Set 3; Quadro Set 5



Load Cell Certifications:



Features:

- NTEP certified load cells from 1Klb-10Klb
- OIML certified load cells from 500kg-10t & 10K-20Klb (QS3);
OIML certified load cells from 1Klb-10Klb (QS5);
- CE, RoHS and ExNepsi certified load cells
- Full Scale Output: 2mV/V \pm 0.25% (QS3);
3mV/V \pm 0.25% (QS5);
- Junction box is equipped with integrated resistor networks
- Cable is coloured in accordance to the ANYLOAD color code

Complete Set:

- 4 pcs x 563YS or 563YS30 Stainless steel single ended shear beam load cells
- 4 pcs x Stainless steel load cell spacers
- 4 pcs x Stainless steel mounting feet AMFSS
- 1 pc x Aluminum junction box J04EA-16
- 1 pc x 20m PVC cable

PART NUMBER

QS3		
Load Cell Capacity	Part No.	Weight (kg) Approx.
250kg	QS3-16-250kg	7.6
500kg	QS3-16-500kg	7.6
1t	QS3-16-1t	7.6
2t	QS3-16-2t	7.6
3t	QS3-16-3t	11.4
5t	QS3-16-5t	11.4
10t	QS3-16-10t	-
500lb	QS3-16-500lb	7.6
1Klb	QS3-16-1Klb	7.6
2.5Klb	QS3-16-2.5Klb	7.6
4Klb	QS3-16-4Klb	7.6
SE5Klb	QS3-16-SE5Klb	7.6
5Klb	QS3-16-5Klb	11.4
10Klb	QS3-16-10Klb	11.4
20Klb	QS3-16-20Klb	-

PART NUMBER

QS5		
Load Cell Capacity	Part No.	Shipping Weight (kg) Approx.
500lb	QS5-GS-16-500lb	7.6
1Klb	QS5-16-1Klb	7.6
2.5Klb	QS5-16-2.5Klb	7.6
4Klb	QS5-16-4Klb	7.6
SE5Klb	QS5-16-SE5Klb	7.6
5Klb	QS5-16-5Klb	11.4
10Klb	QS5-16-10Klb	11.4