



13.2lb x0.002lb
26.4lb x0.005lb
66lb x0.01lb

- Stainless Steel Washdown Construction
- Stainless Steel Load Cell
- NEMA 6P / IP 68 on Ultra Models
- Backlit LCD Display
- Rechargeable Battery
- Food Safe Pillar Design



Ultra Models



| Model | VPS-506G | VPS-512K | VPS-530K | VPS-506GU | VPS-512KU | VPS-530KU |
|---------------------------|--|-----------------------|----------|--|-----------------------|-----------|
| Capacity | 13.2 lb | 26.4 lb | 66 lb | 13.2 lb | 26.4 lb | 66 lb |
| Readability | 0.002 lb | 0.005 lb | 0.01 lb | 0.002 lb | 0.005 lb | 0.01 lb |
| Divisions | 6,000 | 6,000 | 6,000 | 6,000 | 6,000 | 6,000 |
| Weighing Units | g, lb:oz, lb decimal | kg, lb:oz, lb decimal | | g, lb:oz, lb decimal | kg, lb:oz, lb decimal | |
| Functions | Accumulation | | | | | |
| Stabilization Time | < 1.5 seconds | | | | | |
| Tare Range | To capacity by subtraction | | | | | |
| Power Source | Built-in rechargeable battery or external power adapter (included) | | | | | |
| Construction | Stainless steel indicator, base and load cell | | | Stainless steel indicator and base with fully welded and hermetically sealed load cell | | |
| Display | 1 inch / 25.4 mm wide viewing angle LCD backlit display | | | | | |
| Platform Size (W x D x H) | 11 x 13 x 3.7 inches / 280 x 330 x 95 mm | | | | | |
| Dimensions (W x D x H) | 11 x 13 x 17.9 inches / 280 x 330 x 455 mm | | | | | |
| Operating Environment | 32 ° F to 104 ° F non condensing R.H. ≤ 85% | | | | | |
| Net Weight | 15.1 lb / 6.9 kg | | | 15.9 lb / 7.2 kg | | |
| Shipping Weight | 21 lb / 9.5 kg | | | 22 lb / 10 kg | | |
| NEMA / IP Rating | IP 67 | | | IP 68 NEMA 6P | | |

| Features | Benefits |
|---|---|
| All stainless steel platform, pillar, indicator, load cell and base | Easy to clean for food processing or harsh environments / washdown resistant |
| Open pillar design | Allows for thorough washdown with less chance of food particles remaining |
| Heavy duty construction | Will withstand harsh industrial operation |
| Sealed electronics | Improved water and dust resistance |
| Low profile | Easy to load and unload – platform only 3.7 inches / 95 mm high |
| Built-in rechargeable battery or external power adapter | Portability – battery lasts a minimum of 100 hours (without backlight) |
| Accumulation function | Allows you to add together consecutive weights to arrive at a total |
| Zero tracking | Assures that you always start weighing at zero |
| Automatic power save | Conserves battery power |
| Low battery indicator / charge status indicator | Alerts you to charge the battery, saving downtime |
| Easy calibration function | Ensures accuracy |
| Adjustable stainless steel feet with rubber inserts | Scale remains level for accurate results on uneven working surfaces – anti-slip |
| Wide angle LCD display with backlight | Can be seen from a wide viewing angle |

Food Safe Pillar Design
(All Models)



Fully Welded Hermetically Sealed Stainless Steel Load Cell
(Ultra Models: 506GU, 512KU, 530KU)