Specifications

Enclosure:

NEMA Type 4, IP65

Weight:

0.98 lb (445 g)

Keypad:

On/Off, Zero (100%), Tare, Print, and two userdefined keys for the following functions: peak hold, high resolution, total, view total, net/ gross, units switching

Display:

Six-digit 1.0 in (26.4 mm) LCD

Units Displayed:

Pounds, kilograms, tons, metric tons, kilonewtons

Annunciators:

Stable, COZ, low battery, peak, net, kg, kN, lb, M, ton, setpoint, function LEDs $\,$

Power:

Integral lithium ion battery Universal 115/230 VAC, 50/60 Hz battery charger (NA plug included)

Operating Time:

Up to 24 hours of continuous use (15 minute autoshutoff with non-use)

Operating Temperature:

-4°F to 140°F (-20°C to 60°C)

RF Radio Link:

2.4 GHz 802.15.4

Communicates with RF 3460, 4260, 7300, 7000 & 7001

RF Effective Range:

Typically 100 or more feet (33 m)


Connector:

Four-pin Turck connector for charging and RS-232 communication

Warranty:

One-year limited warranty







Standard Features

- · Handheld RF remote display with six-digit 1.0 in (26.4 mm) LCD screen
- · Membrane keypad for remote control functionality
- · User- definable function keys for added versatility
- Universal 115/230 VAC, 50/60 Hz battery charger (NA plug standard)
- Communicates with RF MSI-3460 Challenger 3, MSI-4260 Port-A-Weigh, MSI-7300 Dyna-Link 2, MSI-7000 and MSI-7001 TranSend™

Part Number/Price

| Part # | MSI Part # | Description | Est. Weight | Price |
|--------|-------------|---|-------------|---------|
| 139381 | 503208-0001 | MSI-8000 RF remote display (requires ScaleCore" equipped MSI-7300, MSI-4260, MSI-3460 and TranSend receivers) | 5 lb | Consult |

Options/Accessories

| • | | | | |
|--------|-------------|--|-------------|---------|
| Part # | MSI Part # | Description | Est. Weight | Price |
| 149549 | 503486-0001 | Universal 115/230 VAC 50/60 Hz (NA plug standard) battery charger for MSI-8000 RF remote display | 3 lb | Consult |
| 149550 | 503486-0002 | Universal 115/230 VAC 50/60 Hz (EC plug standard) battery charger for MSI 8000 RF remote display | 1 lb | Consult |
| 150964 | 503489-0001 | DB9 female serial interface cable for MSI-8000 RF remote display | 1 lb | Consult |
| 151095 | 503506-0001 | Audible alarm | _ | Consult |
| 182223 | | 12V car charger adapter for MSI-8000 | 1 lb | Consult |

| Dimensions | | | | | |
|------------|------------------|---|-----------------|--|--|
| Α | 8.00 in (203 mm) | С | 3.85 in (98 mm) | | |
| В | 3.85 in (98 mm) | D | 1.37 in (35 mm) | | |