

NATIONAL TYPE EVALUATION PROGRAM

Certificate of Conformance for Weighing and Measuring Devices

For:

Computing Scale

Model: W-LABEL20 & W-LABEL40L

n_{max}: 4000

 e_{min} : 0.005 kg / 0.01 lb Capacity: 20 kg / 40 lb Platform: 38 cm X 29.7 cm

Accuracy Class: III

Submitted By:

Fabricantes de Básculas Torrey, S. A. de C. V.

/ Fabricantes de Equipos para Refrigeración S.A. de C.V.

Ave. Los Andes #605 Col. Coyoacán Monterrey, Nuevo León, 64510 México

Tel: +52 81 98 1000 ext 126 Contact: Eduardo Zepeda

Email: eduardo.zepeda@torrey.net
Web site: http://www.torrey.net

Standard Features and Options

Automatic Zero Tracking (AZT)
Initial Zero Setting Mechanism (IZSM)
Semi-Automatic Zero (Push Button)
Semi-Automatic Tare (Push Button)
AC Power Supply
Liquid Crystal Display (LCD)
Customer Display (Dual)
Label Printer
RS-232 Communication Port
Ethernet/Wireless Communication

Model	Capacity	d	n _{max}
W-LABEL20	20 kg	0.005 kg	4000
W-LABEL40L	40 lb	0.01 lb	4000

Load Cells Used: Medidata Model M022-20kg (non-NTEP)

Temperature Range: -10 °C to 40 °C (14 °F to 104 °F)

This device was evaluated under the National Type Evaluation Program and was found to comply with the applicable technical requirements of "NIST Handbook 44: Specifications, Tolerances and Other Technical Requirements for Weighing and Measuring Devices." Evaluation results and device characteristics necessary for inspection and use in commerce are on the following pages.

Brett Gurney Chairman, NCWM, Inc.

Committee Chair, National Type Evaluation Program Committee

Issued: January 10, 2019

1135 M Street, Suite 110 / Lincoln, Nebraska 68508





Fabricantes de Básculas Torrey, S. A. de C. V. Computing Scale / W-LABEL20 & W-LABEL40L

Application: For use in general purpose weighing applications.

Identification: The required information is on a label affixed to the scale base beneath the platter.

<u>Sealing</u>: On the side of the unit there is a calibration switch cover that is held in place by two screws. A wire seal is threaded through the two screws to prevent removal of the cover. Additionally, there is an audit trail that has calibration and configuration counters.

To access the audit trail:

With the scale in Zero condition, press the "TARE" button, then the "PROG" button, next you will be asked to enter a password, ("SHOWCOUNTERS") and press "ENTER" The calibration counter is the displayed. Press "ENTER" a second time to view the configuration counter. To exit the audit trail, press "ENTER" again.

<u>Test Conditions</u>: This certificate supersedes Certificate of Conformance Number 16-107 and was issued to recognize a sale of the company to Fabricantes de Equipos para Refrigeracion S.A. de C.V., recognized in the Submitted By: box on page one. Information provided by the manufacturer was reviewed. No additional testing was deemed necessary. Previous test conditions are listed below for reference.

Certificate of Conformance 16-107: For the purposes of this evaluation, a model W-LABEL20 with a 20 x 0.005 kg capacity was submitted. The emphasis of the evaluation was on the design, marking, operation and compliance with influence factor requirements. Several increasing/decreasing load tests and shift tests were performed on each device. The devices were tested with an AC power supply from 102 VAC to 132 VAC. The devices were tested over a temperature range of -10 °C to 40 °C (14 °F to 104 °F). A load of approximately one-half capacity was applied to the units over 100 000 times (each) and the scales were tested periodically during this time.

Evaluated By: E. Morabito (NY) 16-107

<u>Type Evaluation Criteria Used</u>: *NIST Handbook 44 Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices*, 2016 Edition. *NCWM Publication 14 Weighing Devices*, 2016 Edition.

<u>Conclusion</u>: The results of the evaluation and information provided by the manufacturer indicate the device complies with applicable requirements.

Information Reviewed By: J. Truex (NCWM) 16-107, 16-107A1





Fabricantes de Básculas Torrey, S. A. de C. V. Computing Scale / W-LABEL20 & W-LABEL40L

Examples of Device:



W-LABEL20



Wire seal preventing access to calibration switch



Cover open allowing access to calibration switch