

NEW

SINGLE-ENDED BEAM

RL50219SS


Stainless Steel, Environmentally Sealed, IP65

**Dimensions***Picture is a representation of actual product*

Rated Capacity	A	B	C	D	E	F	G	H	I	J
lb/in										
25-500	2.81	1.30	0.62	0.26	0.25	0.50	1.81	1.00	1.00	0.50
kg/mm										
11.3-226.8	71.4	33.0	15.8	6.6	6.4	12.7	46.0	25.4	25.4	12.7

Order Information

Load Rating		Part#	Est. Weight	Price
25 lb	11.3 kg	194014		Consult
50 lb	22.7 kg	194015		Consult
75 lb	34.0 kg	194016		Consult
100 lb	45.4 kg	194017		Consult
150 lb	68.0 kg	194018		Consult
250 lb	113.4 kg	194019		Consult
500 lb	226.8 kg	194020		Consult

**Interchangeable Products**

RICE LAKE WEIGHING SYSTEMS

RL50210 (alloy) page 149**Weigh Module Available**

RICE LAKE WEIGHING SYSTEMS

RL50219SS-TA page 56**Specifications****Full Scale Output:**

3.0 mV/V

Output Resistance:350 (± 3) ohm**Input Resistance:**

380-450 ohm

Material/Finish:

Stainless steel

Temperature:Operating range
0°F to 150°F/-18°C to 65°C**Seal Type:**

Environmentally sealed, IP65

Safe Overload:

150% full scale

Rated Excitation:

5-10 VDC

Nonlinearity:

0.03% full scale

Hysteresis:

0.02% full scale

Combined Error:

0.017% full scale

Insulation Resistance:

5,000 megohms

Cable Length:

20 ft (6.1 m)

Cable Color Code:Red +Excitation
Black -Excitation
Green +Signal
White -Signal**Warranty:**

Two-year limited warranty