Alloy Steel, Environmentally Sealed, NTEP Certified 1:5,000 Class III Multiple Cell, IP66

Interchangeable Products							
RICE LAKE WEIGHING SYSTEMS							
RL35023 page 138							
VPG SENSORTRONICS®							
65023A page 319							
VPG CELTRON®							
SQB page 214							
Weigh Module Available							
RICE LAKE WEIGHING SYSTEMS							
RL50210TA page 52							
RICE LAKE WEIGHING SYSTEMS							
RL1800 Series page 62							

Specifications

Full Scale Output:

3.0 mV/V

Output Resistance:

350 (± 3) ohm

Input Resistance:

400 (\pm 20) ohm

Material/Finish:

Alloy steel, nickel plated

Temperature:

Compensated range:-14°F to 104°F/-10°C to 40°C Operating range: -22° F to 158° F/-30° C to 70° C

Seal Type:

Environmentally sealed, IP66

Safe Overload:

150% full scale

Safe Sideload:

100% full scale

Rated Excitation:

10 VDC (15 V maximum)

Combined Error:

0.017% full scale

Insulation Resistance:

>5,000 megohms

Cable Length:

20ft (6.1 m)

Cable Color Code:

Rea+	EXCITATIO
Black	Excitatio
Green+	Signal
White _	Icani2

Warranty:

Two-year limited warranty

Approvals:







Dimensions

Picture is a representation of actual product

Rated Capacity	Α	В	C	D	E	F	G	Н	I	J	K	L	М	N
lb/in														
250-4,000	1.24	0.59	0.96	2.20	1.24	5.12	0.53	0.70	1/2- 20 UNF	3.00	1.00	0.62	0.25	0.13
5,000-10,000	1.88	-	1.45	2.99	1.63	6.75	0.80	0.70	3/4- 16UNF	3.75	1.50	0.75	-	-
15,000-20,000	-	-	-	-	-	-	-	-	-	-	-	-	-	-
kg/mm														
113.4-1,814.4	31.5	15	24.6	56	31.5	130	13.5	18	1/2- 20 UNF	76.2	25.4	15.8	6.5	3.5
2,268-4,535.9	48	-	37	76	41.5	171.5	20.5	18	3/4- 16UNF	95.2	38.1	19	-	-
6,803.9-9,071.8	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Call Rice Lake for additional information

Order Information

Load Rating		Part#	Est. Weight	Price
250 lb	113.4 kg	189150	2lb	Consult
500 lb	226.8 kg	189151	2lb	Consult
1,000 lb	453.6 kg	189152	2lb	Consult
1,500 lb	680.4 kg	191732	2 lb	Consult
2,000 lb	907.2 kg	189153	2 lb	Consult
2,500 lb	1,134 kg	189154	2 lb	Consult
3,000 lb	1,360.8 kg	189155	5 lb	Consult
4,000 lb	1,814.4 kg	189156	5 lb	Consult
5,000 lb SE	2,268 kg	189157	5 lb	Consult
5,000 lb LE	2,268 kg	189158	5 lb	Consult
10,000 lb	4,535.9 kg	189159	5 lb	Consult
15,000 lb	6,803.9 kg	189160	10 lb	Consult
20,000 lb	9,071.8 kg	189161	10 lb	Consult

