# **NEW**SINGLE-ENDED BEAM

# **RL32018S**

Stainless Steel, Environmentally Sealed, NTEP Certified 1:5,000 Class III Multiple Cell, IP66



## **Dimensions**


Picture is a representation of actual product

<b>Rated Capacity</b>	A	В	C	D	E	F	G	Н	I	J	K	L	M	N
lb/in														
250-4,000	1.24	0.59	0.96	2.20	1.24	5.12	0.53	0.70	1/2- 20 UNF	3.00	1.00	0.62	0.25	0.13
5,000-10,000	1.88	-	1.45	2.99	1.63	6.75	0.80	0.70	3/4- 16UNF	3.75	1.50	0.75	-	-
15,000-20,000	-	-	-	-	-	-	-	-	-	-	-	-	-	-
kg/mm														
113.4-1,814.4	31.5	15	24.6	56	31.5	130	13.5	18	1/2- 20 UNF	76.2	25.4	15.8	6.5	3.5
2,268-4,535.9	48	-	37	76	41.5	171.5	20.5	18	3/4- 16UNF	95.2	38.1	19	-	-
6,803.9-9,071.8	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Call Rice Lake for additional information

## **Order Information**

Load Rating		Part#	Est. Weight	Price
250 lb	113.4 kg	189162	3 lb	Consult
500 lb	226.8 kg	189163	3 lb	Consult
1,000 lb	453.6 kg	189164	3 lb	Consult
2,000 lb	907.2 kg	189165	3 lb	Consult
2,500 lb	1,134 kg	189166	3 lb	Consult
4,000 lb	1,814.4 kg	189167	3 lb	Consult
5,000 lb SE	2,268 kg	189168	3 lb	Consult
5,000 lb LE	2,268 kg	189169	5 lb	Consult
10,000 lb	4,535.9 kg	189170	5 lb	Consult
15,000 lb	6,803.9 kg	189171	10 lb	Consult
20,000 lb	9,071.8 kg	189172	10 lb	Consult



# Interchangeable Products

VPG SENSORTRONICS®

**65023SS**......page 320

VPG CELTRON®

**SQB-HSS** ..... page 215

# Weigh Module Available

RICE LAKE WEIGHING SYSTEMS

**RL50210TA**.....page 52

RICE LAKE WEIGHING SYSTEMS

RL1800 Series..... page 62

## **Specifications**

# Full Scale Output:

 $3.0\,\text{mV/V}$ 

#### **Output Resistance:**

350 ( $\pm$  3) ohm

## Input Resistance:

400 (± 20) ohm

#### Material/Finish: Stainless steel

#### Temperature:

Compensated range: 14° F to 104° F/-10° C to 40° C Operating range: -40° F to 150° F/-40° C to 65° C

#### Seal Type:

Environmentally sealed, IP66

## Safe Overload:

150% full scale

#### **Rated Excitation:**

10 VDC (15 V maximum)

## **Combined Error:**

0.017% full scale

#### **Insulation Resistance:**

>5,000 megohms

# Cable Length:

20 ft (6.1 m)

#### **Cable Color Code:**

Red+	Excitation
Black	Excitation
Green+	Signal
White	Signal

## Warranty:

Two-year limited warranty

#### Approvals:



