

Interchangeable Products

RICE LAKE WEIGHING SYSTEMS

RL70000SS page 154

VPG REVERE®

9103 page 292**Weigh Module Available**

RICE LAKE WEIGHING SYSTEMS

EZ Mount 1 page 84**Specifications****Full Scale Output:**

3.0 mV/V, nominal

Output Resistance:700 \pm 5 ohm**Input Resistance:**780 \pm 10 ohm**Material/Finish:**

Stainless steel

Temperature:

Compensated range

0°F to 150°F/-18°C to 65°C

Operating range

-40°F to 150°F/-40°C to 65°C

Safe Overload:

150% full scale

Safe Sideload:

100% full scale

Non Linearity:

0.03% full scale

Hysteresis:

0.05% full scale

Rated Excitation:

5-15 VDC

Insulation Resistance:

5,000 megohms

Cable Diameter:

0.190 polyurethane jacket

Cable Color Code:

Red+ Excitation

Black.....- Excitation

Green+ Signal

White- Signal

OrangeShield

Seal Type:

Hermetically sealed, IP68

Cable Length:

25 ft (7.6 m)

Warranty:

Two-year limited warranty

Approvals:**Dimensions***Picture is a representation of actual product*

Rated Capacity	A	B	C	D	E	F	ØG	H
lb/in								
5,000-20,000	8.12	1.14	6.88	1.44	1.71	1.71	1.00	1/4-18 NPT
30,000-60,000	10.25	2.38	8.50	1.88	3.03	3.03	2.00	1/2-14 NPT
kg/mm								
2,268.0-9,071.9	206.2	28.9	174.7	36.5	43.43	43.43	25.4	1/4-18 NPT
13,607.8-27,215.5	260.3	60.4	215.9	47.7	76.96	76.96	50.8	1/2-14 NPT

Order Information

Load Rating		Part#	Est. Weight	Price
5000 lb	2,268.0 kg	118462	5 lb	Consult
10,000 lb	4,535.9 kg	118463	5 lb	Consult
20,000 lb	9,071.9 kg	118464	5 lb	Consult
30,000 lb	13,607.8 kg	118465	20 lb	Consult
40,000 lb	18,143.7 kg	118466	20 lb	Consult
50,000 lb	22,679.6 kg	118467	20 lb	Consult
60,000 lb	27,215.5 kg	118468	20 lb	Consult

